



PETROL INTAKE & EGR CLEANER

PIC250



PRO WORKSHOP®

PRODUCT FEATURES:

- Improves performance & economy
- Removes carbon & varnish deposits
- Ensures longevity of vital components
- Restores optimum airflow into the combustion chamber
- Recommended to be used at each service to maintain cleanliness

DESCRIPTION:

Effectively cleans the entire air intake system.

DIRECTIONS FOR USE:

1. Warm up engine, remove the air filter or an access vacuum line
2. Run engine up to 2000 rpm
3. Spray product with short sprays of 1 to 2 seconds into the air intake manifold
4. After each spray, it is normal for the RPM to decrease and then increase again. Ensure that the original RPM is restored prior to repeating the process again.
5. Continue the process until the aerosol can has been fully exhausted & then apply some short bursts to the throttle to ensure all product has been used
6. Leave the engine running for at least five minutes after the last acceleration.
7. Stop the engine & reinstall the intake hose.
8. Start engine and drive the vehicle for 5 minutes and avoid overloading the engine

SPECIFICATIONS:

Appearance: Clear, colourless to light yellow liquid

Transparency: Transparent

Density: ~0.848 g/cm³ (@ 20°C)

ORDERING INFORMATION:

CODE	PACK SIZE	QTY/CARTON
PIC250	250gr aerosol	12 cans per carton

WARRANTY: All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation, and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

