PRODUCT DATA SHEET

EXTREME PERFORMANCE GREASE

PRO CONSUMABLES

PRODUCT FEATURES:

- SUPERIOR PERFORMANCE UNDER PRESSURE
  Outperforms standard greases to ensure reliable protection in demanding operating conditions.
- EXCEPTIONAL WEAR AND WATER RESISTANCE
  Forms a durable protective barrier that shields components in harsh, high moisture environments.
- REDUCED CONSUMPTION & LONGER SERVICE LIFE
  Maintains effectiveness over extended intervals, helping lower maintenance costs and minimise downtime.

DESCRIPTION:

Extreme Performance Grease is the product of choice when onlythe highest quality lubrication will do, especially in extreme pressure applications.

Formulated with a high-quality calcium sulphonate thickenerand an advanced base oil package, it delivers market leading protection in applications exposed to heavy wear andwater washout.It is able to deliver exceptional performance & durability across a wide variety of uses, except for high-speed applications.

Contains calcium sulphonate which provides superior wear protection and exceptional water resistance.

SPECIFICATIONS:

Thickener		Calcium sulfonate complex
Base Fluid		Mineral oil
Texture		Smooth
Color	Visual	Green
NLGI Grade	ASTM D 217	2
Dropping Point	IP 396	>280 °C
Base oil viscosity @ 40 °C	ASTM D 7152	290 mm2/s
Base oil viscosity @ 100 °C	ASTM D 7152	18 mm2/s
Penetration 60 strokes	ISO 2137	265-295
4-ball weld load	DIN 51350:4	7500N
4-ball weld load	ASTM D 2596	800 kgf
Water resistance at 90°C	DIN 51807:1	1
Water wash out at 79°C	ISO 11009	<10 %
Water spray off	ASTM D 4049	40%
Emcor salt water °C	ISO 11007	≤1-1
Flow Pressure at -30 °C	DIN 51805 mod	<1400 mbar
SKF R2F B at 140°C	SKF	Pass
Density	IP 530	1020 kg/m3
Temperature range:		-30 °C to +180 °C

ORDERING INFORMATION:

CODE	PACK SIZE	QTY/CARTON
EPG450	450g	20 tubes
EPG500	500g	12 shuttle cartridges
EPG20	20kg	1
EPG180	180kg	1



WARRANTY: All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation, and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.