PRODUCT DATA SHEET

EXTREME HI-TEMP GREASE

500g Shuttle

PRO CONSUMABLES

PRODUCT FEATURES:

- DELIVERS SUPERIOR PERFORMANCE compared to standard greases, ensuring reliable protection in demanding conditions.
- VERSATILE ACROSS A WIDE RANGE OF APPLICATIONS, making it suitable for mixed fleets, industrial equipment, and general workshop use.
- REDUCES OVERALL GREASE CONSUMPTION by maintaining effectiveness for longer service intervals, helping lower maintenance costs and downtime.

DESCRIPTION:

Extreme Hi-Temp Grease is a speciality, high performance grease designed for demanding applications, especially in high temperatures & where superior protection is desired.

Formulated with a high quality lithium complex thickener and advanced base oil package, it incorporates our unique "Extreme Protection Technology" to deliver exceptional performance & durability across a wide range of operating conditions.

"Extreme Protection Technology" is formulated to provide additional boundary lubrication by bonding to metal surfaces, reducing friction & wear to ultimately extend the life of vital components

SPECIFICATIONS:

Appearance		Smooth grease
Colour		Red
NLGI Classification		2
Thickener		Lithium Complex
Base Oil		Solvent refined mineral oil
Kinematic Viscosity cSt @ 40°C	IP 71	320
Worked penetration	IP 50	265 to 295
Dropping point °C	IP 132	250 min
Copper corrosion	IP 112	Pass
Water washout @ 38 °C %	IP 215	3
Four Ball Weld Load kgs	IP 239	500
Wear load index		62
Operating Temperature range		-20 °C to 150 °C

ORDERING INFORMATION:

CODE	PACK SIZE	QTY/CARTON
EHT500	500g	12 shuttle cartridges



WARRANTY: All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation, and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.