PRODUCT DATA SHEET

EXTREME HI-TEMP GREASE

400g, 450g, 2.5kg, 20kg, 180kg

PRO CONSUMABLES

PRODUCT FEATURES:

- DELIVERS SUPERIOR PERFORMANCE compared to standard greases, ensuring reliable protection in demanding conditions.
- VERSATILE ACROSS A WIDE RANGE OF APPLICATIONS, making it suitable for mixed fleets, industrial equipment, and general workshop use.
- REDUCES OVERALL GREASE CONSUMPTION by maintaining effectiveness for longer service intervals, helping lower maintenance costs and downtime.

DESCRIPTION:

Extreme Hi-Temp Grease is a speciality, high performance grease designed for demanding applications, especially in high temperatures & where superior protection is desired.

Formulated with a high quality lithium complex thickener and advanced base oil package, it incorporates our unique “Extreme Protection Technology” to deliver exceptional performance & durability across a wide range of operating conditions.

“Extreme Protection Technology” is formulated to provide additional boundary lubrication by bonding to metal surfaces, reducing friction & wear to ultimately extend the life of vital components

SPECIFICATIONS:

NLGI Grade		2
Colour		Red
Soap Thickener		Lithium Complex
Base Oil		Mineral
Penetration, worked (60 strokes @25C)	ASTM D217	268
Base Oil Viscosity @40C (cSt)	ASTM D445	320
Weld Load Point @ kgf (sec)	ASTM D2596	500
Oil Separation (%)	ASTM D6184	<2.0
Water Washout @ 79C (%)	ASTM D1264	2.7
Drop Point (C)	ASTM D2265	250+
Operating Temperature Range (C)	ASTM D4950	-20 to 160



ORDERING INFORMATION:

CODE	PACK SIZE	QTY/CARTON
EHT400	400g	20 tubes
EHT450	450g	20 tubes
EHT25	2.5kg	1
EHT20	20kg	1
EHT180	180kg	1

WARRANTY: All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation, and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.